


# Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

ROCKWOOL® Passive fire insulation for the Nordic market



EPD-Global

**Owner of the declaration:**  
ROCKWOOL Nordics

**Product:**  
ROCKWOOL® Passive fire insulation for the Nordic market

**Declared unit:**  
1 m<sup>2</sup>

**This declaration is based on Product Category Rules:**

CEN Standard EN 15804:2012+A2:2019 serves as core PCR. NPCR Part A Construction products and services. NPCR 012:2022 Part B for Thermal insulation products

**Program operator:**  
EPD-Global

**Declaration number:**  
NEPD-4119-3333

**Issue date:**  
03.01.2023

**Latest revision**  
v1.1 Date: 29.12.2025

**Valid to:**  
03.01.2028

**EPD software:**  
LCAno EPD generator ID: 1378026

## General information

### Product

ROCKWOOL® Passive fire insulation for the Nordic market

### Program operator:

EPD-Global  
Post Box 5250 Majorstuen, 0303 Oslo, Norway  
Phone: +47 977 22 020  
web: [www.epd-global.com](http://www.epd-global.com)

### Declaration number:

NEPD-4119-3333

### This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR. NPCR Part A Construction products and services.  
NPCR 012:2022 Part B for Thermal insulation products

### Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD-Global shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

### Declared unit:

1 m<sup>2</sup> ROCKWOOL® Passive fire insulation for the Nordic market

### Declared unit with option:

A1-A3, A4, A5, C1, C2, C3, C4, D

### Functional unit:

Functional Unit Comparability:  
The specific product, referred to in the declared unit is 1 m<sup>2</sup> Conlit 150 P (without fleece) passive fire insulation with a thermal resistance R=1m<sup>2</sup>K/W for the Nordic market. The referenced product is 39 mm thick with a density of 165 kg/m<sup>3</sup>. The weight of the referenced product corresponding to the declared unit is 6,4 kg.

The impact indicators for another specific product can be calculated by multiplying the results of the EPD with the respective scaling factor from a range of products covered by this EPD. A table with the different products available in the portfolio and their respective scaling factors is provided within the 'Technical information' section.

### General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Global, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Global's General Programme Instructions for further information on EPD tools

### Verification of EPD tool:

### Owner of the declaration:

ROCKWOOL Nordics  
Contact person: Christian J. Kofod  
Phone: +45 4656 1616  
e-mail: [info@rockwool.com](mailto:info@rockwool.com)

### Manufacturer:

ROCKWOOL Nordics  
Hovedgaden 501  
DK-2640 Hedehusene, Denmark

### Place of production:

ROCKWOOL factories Doense and Vamdrup (Biomethane line), Denmark; Moss (Electrical melter) Norway

### Management system:

ISO 14001, ISO 9001

### Organisation no:

CVR nr. 42391719

### Issue date:

03.01.2023

### Valid to:

03.01.2028

### Year of study:

2021

### Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804:2012+A2:2019 and seen in a building context.

### Development and verification of EPD:

The declaration is created using EPD tool Ica.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD-Global.

Developer of EPD: Amalie Leanda Pajbjerg

Reviewer of company-specific input data and EPD: Christian Julius Kofod

### Approved:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPD-Global's procedures and guidelines for verification and approval of EPD tools.

A handwritten signature in blue ink that reads "Håkon Hauan".

Håkon Hauan, CEO EPD-Global

Third party verifier:

Jane Anderson, Construction LCA Ltd

(no signature required)

## Product

### Product description:

This EPD documents the potential environmental impacts of 1 m<sup>2</sup> of ROCKWOOL Conlit 150 P stone wool passive fire insulation with a thermal resistance (R-value) equal to 1 m<sup>2</sup>K/W. The intended use of the EPD is to communicate quantified environmental impacts of construction products for application in the assessment of the environmental performance of buildings.

### Product specification

The average composition used for this EPD is calculated based on average factory consumption figures for raw materials. The raw materials are mainly non-scarce stones, and resin binder.

Materials	Value	Unit
Stone wool fibre		
Binder		
Water repellency oil		

### Technical data:

For the products covered by this EPD, the performance data are in accordance with the declaration of performance with respect to its essential characteristics according to EN 13162:2012+A1:2015, "Thermal insulation products for buildings – Factory made mineral wool (MW) products – Specification".

- Thermal conductivity: 0,035 - 0,040 W/mK, reference standards: EN 12939 and EN 12667

- Fire class: A1 or NPD (No Performance Declared), reference standard: EN 13501-1:2007+ A1:2009

A full overview of the technical specifications can be found on the local rockwool website.

Scaling factor can be used to estimate the environmental performance indicators for specific products.

Scaling factors for ROCKWOOL passive fire insulation covered by this EPD as specified by the conditions given in this EPD can be calculated per following formula:

Calculation of product specific scaling factors

Reference product:

Name: Conlit 150 P (w/o fleece)

Density: 165 kg/m<sup>3</sup>

Lambda: 0,039 W/mK

Per 1 m<sup>2</sup> (R=1):  $\text{Density, scaled product (kg/m}^3\text{)} * \text{Lambda, scaled product (W/mK)} / \text{Density, reference product (kg/m}^3\text{)} * \text{Lambda, reference product (W/mK)} = \text{Density, scaled product (kg/m}^3\text{)} * \text{Lambda, scaled product (W/mK)} * 0,16$

Per 1 m<sup>3</sup>:  $\text{Density, scaled product (kg/m}^3\text{)} / \text{Density, reference product (kg/m}^3\text{)} * \text{Lambda, reference product (W/mK)} = \text{Density, scaled product (kg/m}^3\text{)} * 0,16$

Scaling factors for listed ROCKWOOL passive fire insulation products:

AF: Alu Foil / KF : Kraft Paper / NGF: Nonwoven Glass Fleece / SM : Steel Mesh / N : No facing

Scaling factors only include mineral wool core.

Product	Facing	Density (kg/m <sup>3</sup> )	Lambda (W/mK)	Scaling factor per m <sup>2</sup> (R=1)	Scaling factor per m <sup>3</sup>
Conlit 120	NGF	130	0.037	0.7	19
Conlit 150 Alu	AF	165	0.039	1.0	26
Conlit 150 P w/o fleece	N	165	0.039	1.0	26
Conlit 150 w fleece	NGF	165	0.039	1.0	26
Conlit 300	N	300	0.04	1.9	48
Conlit Fire Board EI 30	AF	111	0.036	0.6	17
Conlit Fire Board EI 60	AF	167	0.036	0.9	25
Conlit Fire Board EI 90	AF	200	0.036	1.1	31
Conlit Fire Board EI 120	AF / SM	200	0.036	1.1	31
Conlit Fire Mat EI 15	AF / SM	90	0.035	0.5	14
Conlit Fire Mat EI 30	AF / SM	70	0.035	0.4	11
Conlit Fire Mat EI 60	AF / SM	80	0.035	0.4	11
Conlit Fire Mat EI 90	NGF / SM	80	0.035	0.4	11
Conlit Fire Mat EI 120	NGF / SM	80	0.035	0.4	11
Conlit Fire Mat Comfort EI 15	NGF / SM	90	0.035	0.5	14
Conlit Fire Mat Comfort EI 30	NGF / SM	70	0.035	0.4	11
Conlit Fire Mat Comfort EI 60	NGF / SM	80	0.035	0.4	11
Conlit Fire Mat Comfort EI 90	NGF / SM	80	0.035	0.4	11
Conlit Fire Mat Comfort EI 120	NGF / SM	80	0.035	0.4	11
Conlit Rørskål/Brandbøsning	AF	165	0.038	1.0	26

### Market:

This EPD is intended for the Nordic market. The EPD can be used in specific Nordics markets by adjusting the A4 module to reflect correct transportation distance.

### Reference service life, product

ROCKWOOL® stone wool thermal insulation products are extremely durable and provide effective performance for the lifetime of a building or host structure, with no need to be replaced. The thermal, fire-resistance, and acoustic performance of ROCKWOOL® stone wool products, when correctly installed, remains the same during 60 years reference service life or as long as the insulation is part of the building.

### Reference service life, building or construction works

In this EPD, the reference service life of a building is set to 60 years.

### LCA: Calculation rules

#### Declared unit:

1 m<sup>2</sup> ROCKWOOL® Passive fire insulation for the Nordic market

#### Cut-off criteria:

All major raw materials and all the essential energy are included. All hazardous materials and substances are considered in the inventory. Data sets within the system boundary are complete and fulfil criteria for the exclusion of inputs and output criteria. All data, materials and energy consumptions, have been specified according to the production data and have been considered within the inventory analysis.

#### Allocation:

The allocation is made in accordance with the provisions of EN 15804+A2. Production activities, electricity and energy consumption and waste generation are allocated equally among all products from the production site through mass allocation.

#### Data quality:


All data represents the applicable geography, time and technology for the specific and generic data, generally assessed as good and very good. Primary data are collected from the specific production sites, in the reference year 2021 and represent stabilized production. Generic data is from GaBi database (version 2021) with GaBi Software version 10.0.1.92.

## System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	X

### System boundary:

The LCA is performed as a 'cradle-to-grave' study, addressing all life cycle stages identified in the EN 15804+A2. All major raw materials, energy, electricity use and waste are included for all life cycle modules, see flowchart below. Use stage B1-7 modules are considered but are not relevant, as there are no activities and no significant environmental impact in the use stage.



## LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

The EPD is based on LCA inventory data from the producing factories. The reference flow is a weighted average based on the distribution of production capacity

Transport from production place to assembly/user (A4)

The A4 distance is calculated as weighted average distance for the Nordic market

Assembly (A5)

In A5 the default installation is assumed to be manual, therefore no energy consumption or ancillary equipment is needed. The product waste from installation is assumed to be 2% and according to the modularity principle of EN 15804+A2 its impacts are fully allocated to A5, following same EoL scenario as in C. The A5 module includes also the corresponding end-of-life considerations for packaging (10 % landfill). The credits from heat and electricity recovery from incineration or material recycling from module A5 (90% recycling and energy recovery) are attributed to module D.

Use stage (B1, B2, B3, B4, B5, B6, B7)

There are no consumables and no maintenance (B2), repair (B3), replacements (B4) or refurbishments (B5) required during the use of ROCKWOOL® thermal insulation products in standard conditions. They do not use energy (B6) or water (B7) during their operational life. No LCA: Scenarios and additional technical information EPD for the best environmental decision 8 significant emissions to the indoor environment occur in module (B1). Therefore, modules B1- B7 are not relevant for this EPD.

Benefits and loads beyond the system boundaries (D)

Benefits in module D are created from packaging materials treatment after installation and recycling potential of stone wool in the end of life. Quantities of packaging materials include both recycled materials and materials sent for energy recovery. Recycling potential of net stone wool material is considered here.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Container ship, 5,000 to 200,000 dwt payload capacity, ocean going (kgkm)	40.0 %	141.00	0.004	l/tkm	0.56
Transport from Doense: Truck, Euro 6, 27t payload (kgkm)	30.0 %	19.00	0.019	l/tkm	0.36
Transport from Moss: Truck, Euro 6, 27t payload (kgkm)	30.0 %	38.00	0.019	l/tkm	0.72
Transport from Vamdrup: Truck, Euro 6, 27t payload (kgkm)	30.0 %	262.00	0.019	l/tkm	4.98
Transport from production place to user (A4)	Unit	Value			
Truck, Euro 6	km	320			
Ship container	km	141			
Assembly (A5)	Unit	Value			
Auxiliary	kg	0.00			
Water consumption	m <sup>3</sup>	0.00			
Electricity consumption	kWh	0.00			
Other energy carriers	MJ	0.00			
Material loss	kg	0.128			
Cardboard and paper packaging	kg	0.02896			
Plastic packaging	kg	0.06081			
Wood packaging	kg	0.3191			
Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Waste transport, Denmark, DOE: Truck, Euro 6 (kgkm)	50.0 %	9.00	0.025	l/tkm	0.23
Waste transport, Denmark, VAM: Truck, Euro 6 (kgkm)	50.0 %	123.00	0.025	l/tkm	3.08
Waste transport, Norway: Truck, Euro 6 (kgkm)	50.0 %	18.00	0.025	l/tkm	0.45
Waste processing (C3)	Unit	Value			
Sent for reuse	kg	0.384			
Sent for recycling	kg	0.105			
Energy recovery	kg	0.0384			
Hazardous waste disposed	kg	0.00			
Collected as mixed construction waste	kg	6.02			
Disposal (C4)	Unit	Value			
Collected as mixed construction waste	kg	0.00			
Sent to landfill	kg	6.26			
Hazardous waste disposed	kg	0.00			
Benefits and loads beyond the system boundaries (D)	Unit	Value			
Packaging recycled	kg	0.0923			
Energy recovered	MJ	2.18			

## LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact										
Indicator		Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
	GWP-total	kg CO <sub>2</sub> -eq	2.55E+00	2.09E-01	6.15E-01	0	2.06E-02	0.00E+00	9.48E-02	-2.25E-01
	GWP-fossil	kg CO <sub>2</sub> -eq	3.05E+00	2.07E-01	1.08E-01	0	2.05E-02	0.00E+00	9.45E-02	-2.52E-01
	GWP-biogenic	kg CO <sub>2</sub> -eq	-5.06E-01	0.00E+00	5.06E-01	0	0.00E+00	0.00E+00	0.00E+00	2.75E-02
	GWP-luluc	kg CO <sub>2</sub> -eq	2.68E-03	1.60E-03	1.04E-04	0	1.69E-04	0.00E+00	2.78E-04	-1.26E-04
	ODP	kg CFC11 -eq	1.77E-08	0.00E+00	9.25E-10	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	AP	mol H+ -eq	6.02E-02	6.67E-04	1.36E-03	0	2.17E-05	0.00E+00	6.76E-04	-5.85E-04
	EP-FreshWater	kg P -eq	4.20E-05	3.09E-06	1.26E-06	0	6.16E-08	0.00E+00	1.59E-07	-4.28E-07
	EP-Marine	kg N -eq	6.99E-03	1.77E-04	1.98E-04	0	7.13E-06	0.00E+00	1.75E-04	-1.37E-04
	EP-Terrestrial	mol N -eq	2.46E-01	1.99E-03	5.47E-03	0	8.48E-05	0.00E+00	1.92E-03	-1.47E-03
	POCP	kg NMVOC -eq	1.45E-02	4.99E-04	4.25E-04	0	1.90E-05	0.00E+00	5.30E-04	-4.19E-04
	ADP-minerals&metals <sup>1</sup>	kg Sb-eq	1.42E-06	1.26E-08	3.26E-08	0	1.92E-09	0.00E+00	8.94E-09	-3.39E-08
	ADP-fossil <sup>1</sup>	MJ	3.59E+01	2.76E+00	1.26E+00	0	2.74E-01	0.00E+00	1.26E+00	-5.56E+00
	WDP <sup>1</sup>	m <sup>3</sup>	5.65E-01	1.71E-03	6.40E-02	0	1.79E-04	0.00E+00	1.01E-02	-6.71E-02

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

Reading example: 9.0 E-03 = 9.0\*10<sup>-3</sup> = 0.009

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.

### Remarks to environmental impacts

The main GWP contribution from the product life cycle is linked to the Product stage (A1-A3). This is primarily related to the materials delivered to the factory gate and consumption of energy.

The CO<sub>2</sub> absorbed by the wood in the wooden pallets is represented by a negative GWPbiogenic.

The GWP-Biogenic, e.g. the carbon stored in the wooden pallets, is released during the construction stage phase (A5) where the wood is presumed incinerated with energy recovery.

The benefits from energy recovery (a negative GWP) from incineration of packaging materials (wood pallets and plastic foils) is allocated to Benefits & Loads beyond system (D).

Impacts linked to end of life stages (C1-C4) are primarily linked to transportation of stone wool to recycling or to landfill.

Melting virgin materials or re-melting returned ROCKWOOL stone wool are both similarly energy intensive processes. Increasing the recycling rate for return wool, will therefore not lead to great variations in the overall GWP profile. However, increased recycling will be linked directly to reduction of waste sent to landfill.

Additional environmental impact indicators										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
 PM	Disease incidence	4.78E-07	1.02E-08	1.07E-08	0	0.00E+00	0.00E+00	8.37E-09	-9.22E-09	
 IRP <sup>2</sup>	kgBq U235 -eq	3.44E-02	4.75E-04	5.67E-03	0	4.76E-05	0.00E+00	1.38E-03	-5.09E-03	
 ETP-fw <sup>1</sup>	CTUe	1.24E+01	1.99E+00	5.00E-01	0	1.99E-01	0.00E+00	7.15E-01	-2.50E-01	
 HTP-c <sup>1</sup>	CTUh	5.56E-09	0.00E+00	1.24E-10	0	0.00E+00	0.00E+00	1.08E-10	-3.00E-11	
 HTP-nc <sup>1</sup>	CTUh	2.14E-08	2.04E-09	1.64E-09	0	0.00E+00	0.00E+00	1.16E-08	-1.20E-09	
 SQP <sup>1</sup>	dimensionless	9.57E+01	8.92E-01	2.01E+00	0	9.44E-02	0.00E+00	2.53E-01	-5.49E+00	

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

Reading example:  $9.0 \text{ E-}03 = 9.0 \cdot 10^{-3} = 0.009$

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
 PERE	MJ	1.16E+02	1.46E-01	2.60E+00	0	1.54E-02	0.00E+00	1.69E-01	-1.25E+00	
 PERM	MJ	5.47E+00	0.00E+00	-1.64E-01	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
 PERT	MJ	1.22E+02	1.46E-01	2.43E+00	0	1.54E-02	0.00E+00	1.69E-01	-1.25E+00	
 PENRE	MJ	3.35E+01	2.76E+00	1.29E+00	0	2.75E-01	0.00E+00	1.26E+00	-5.58E+00	
 PENRM	MJ	2.45E+00	0.00E+00	-7.35E-02	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
 PENRT	MJ	3.60E+01	2.76E+00	1.21E+00	0	2.75E-01	0.00E+00	1.26E+00	-5.58E+00	
 SM	kg	1.24E-02	0.00E+00	2.49E-04	0	0.00E+00	0.00E+00	0.00E+00	-1.29E-01	
 RSF	MJ	0.00E+00	0.00E+00	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
 NRSF	MJ	0.00E+00	0.00E+00	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
 FW	m <sup>3</sup>	1.48E-02	1.66E-04	1.58E-03	0	1.75E-05	0.00E+00	3.10E-04	-1.99E-03	

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

Reading example: 9.0 E-03 = 9.0\*10<sup>-3</sup> = 0.009

End of life - Waste										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
 HWD	kg	1.43E-06	0.00E+00	5.36E-09	0	0.00E+00	0.00E+00	1.33E-10	-1.75E-09	
 NHWD	kg	1.82E-01	4.02E-04	5.38E-02	0	4.09E-05	0.00E+00	6.26E+00	-1.55E-02	
 RWD	kg	1.50E-04	3.32E-06	3.93E-05	0	3.33E-07	0.00E+00	1.31E-05	-4.29E-05	

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

Reading example: 9.0 E-03 = 9.0\*10<sup>-3</sup> = 0.009

End of life - Output flow										
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
 CRU	kg	0.00E+00	0.00E+00	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
 MFR	kg	0.00E+00	0.00E+00	1.19E-01	0	0.00E+00	1.29E-01	0.00E+00	0.00E+00	
 MER	kg	0.00E+00	0.00E+00	2.22E-03	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
 EEE	MJ	0.00E+00	0.00E+00	5.45E-01	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	
 EET	MJ	0.00E+00	0.00E+00	1.64E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00	

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

Reading example: 9.0 E-03 = 9.0\*10<sup>-3</sup> = 0.009

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0.00E+00
Biogenic carbon content in accompanying packaging	kg C	1.53E-01

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO<sub>2</sub>.

## Additional requirements

### Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Source	Amount	Unit
Electricity, wind power, Denmark (kWh)	GaBi (version 2021)	6.00	g CO <sub>2</sub> -eq/kWh
Electricity, hydro power, Norway (kWh)	GaBi (version 2021)	14.00	g CO <sub>2</sub> -eq/kWh

### Dangerous substances

The product contains no substances given by the REACH Candidate list. The product is classified as hazardous waste, see table:

### Indoor environment

There are no legal requirements for indoor emissions of stone wool thermal insulation products.

## Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products									
Indicator	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWPIOBC	kg CO <sub>2</sub> -eq	3.05E+00	2.09E-01	1.08E-01	0	2.07E-02	0.00E+00	9.48E-02	-2.52E-01

GWPI-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

## Bibliography

- ISO 14025:2010 - Environmental labels and declarations - Type III environmental declarations - Principles and procedures
- ISO 14044:2006 - Environmental management - Life cycle assessment - Requirements and guidelines
- EN 15804:2012+A2:2019 - Sustainability of construction works - Environmental product declaration - Core rules for the product category of construction products
- EN 12939:2000 - Thermal performance of building materials and products - Determination of thermal resistance by means of guarded hot plate and heat flow meter methods - Thick products of high and medium thermal resistance
- EN 12667:2001 - Thermal performance of building materials and products – determination of thermal resistance by means of guarded hot plate and heat flow meter methods – Products of high and medium thermal resistance
- EN 13501-1:2007+A1:2009 - Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests
- ISO 21930:2007 - Sustainability in building construction - Environmental declaration of building products
- PCR - NPCR Part A Construction products and services
- PCR - NPCR 012:2022 version 2.0. Part B for Thermal insulation products
- Larisa Xanthopoulou - Background LCA report for EPDs ROCKWOOL Nordics, Feb. 2022
- Larisa Xanthopoulou - ROCKWOOL Rules for publishing EPDs, ver.3, December 2021

 Powered by EPD-Norway	<b>Program operator and publisher</b> EPD-Global Postboks 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 977 22 020 e-mail: <a href="mailto:post@epd-norge.no">post@epd-norge.no</a> web: <a href="http://www.epd-global.com">www.epd-global.com</a>
	<b>Owner of the declaration:</b> ROCKWOOL Nordics Hovedgaden 501, DK-2640 Hedehusene, Denmark	Phone: +45 4656 1616 e-mail: <a href="mailto:info@rockwool.com">info@rockwool.com</a> web: <a href="http://www.rockwool.dk">www.rockwool.dk</a>
	<b>Author of the Life Cycle Assessment</b> LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: <a href="mailto:post@lca.no">post@lca.no</a> web: <a href="http://www.lca.no">www.lca.no</a>
	<b>Developer of EPD generator</b> LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: <a href="mailto:post@lca.no">post@lca.no</a> web: <a href="http://www.lca.no">www.lca.no</a>
	ECO Platform ECO Portal	web: <a href="http://www.eco-platform.org">www.eco-platform.org</a> web: ECO Portal