

Building product declaration

according to BPD associations' standardised format eBVD

2025-03-07 10:10:27

Flexilight PRO

1. COMPANY INFORMATION

BMI Sverige AB

Company name:	Organisation number:			
BMI Sverige AB	556013-0709			
Address:	Contact person:			
Pulpetgatan 20	Lars Åhsberg			
E-mail:	Telephone:			
lars.ahsberg@bmigroup.com	070-6045046			
VAT number:	Website:			
	https://bmisverige.se/			
GLN:	DUNS:			
Company was last saved				
2024-12-11 09:55:43				
Company's certification				
✓ ISO 9001				
Other:				
Bitumentätskiktproduktionen i Malmö är certifierad enligt ISO 9001.				
Policies and guidelines				
The company has a code of conduct/policy/guidelines for dealing with the requirements	social responsibility in the supplier chain, including procedures for ensuring			
This is third-party audited				
If yes, which if the following guidelines have you affiliated to or management	system you have implemented			
✓ UN guiding principles for companies and human rights				
ILO's eight core conventions				
OECD Guidelines for Multinational Enterprises				
✓ UN Global Compact				
ISO 26000				
Other policy guidelines				

Management system

If you have a management system for corporate social responsibility, what out of the following is included in the work?

Mapping	
Risk analysis	
Action plan	
Monitoring	
Sustainability reporting guidelines:	Susta
nligt Årsredovisningslagen (1995:554)	Enlig

2. ARTICLE INFORMATION

Document data

ld:	Version:
C-SE556013070901-92	3
Created:	Last saved:
2025-03-07 10:06:50	2025-03-07 10:10:27
Changes relates to:	
Justering av innehållsdeklarationen.	
Flexilight PRO	
Article name:	
Flexilight PRO	
Article No/ID concept	
Article identity: GTIN	
7391738012957	
Article identity: VAT-ID	
SE10006458 01- 10 006 459	

Product group/Product group classification

Product group system	Product group id
ВК04	01409

Article description:

Flexilight underlagsduk används under falsade överläggsplattor (t ex takpannor av betong, tegel eller plåt) på underlag av trä. Duken fungerar som vattenavledande skikt enligt kraven i AMA Hus JSC.61. Klass UD2. Flexilight tillverkas i Sverige för våra specifika byggtraditioner och klimatförhållanden. Underlagsduken är åldringsbeständig och diffusionstät. Stommen är belagd med SBS-modifierad bitumen som gör produkten smidig att hantera även vid låga temperaturer. Under- och översida skyddas av en filt av polypropen.

Flexilight PRO kan användas på taklutningar ända ned till 3°. Produkten är sandfri med en materialvikt på 750 g/m2. Flexilight PRO har 1,20 m breda våder som ger snabb läggning. Materialsammansättningen gör den följsam att jobba med även vid kall väderlek, med självhäftande klisterkanter av bitumen i båda sidor som ger ett extra starkt förband. Flexilight PRO är testad enligt utökade krav för vattentäthet. Den klarar belastning utöver klass W1, med vattentryck

av 1 m vattenpelare 24 timmar. Exponeringstid max 3 månader. Ånggenomgångsmotstånd ca Zv 2200x103 s/m eller Sd 58 m.

Declarations of performance:

Yes

Declaration of performance number:

060-1210

Other information:

3. CHEMICAL CONTENT

Chemical content

Does the declaration apply to a product or chemical product?

product

Enter chemical content for the whole article. The concentration is calculated at component level according to the principle of "once an article always an article".

Is there a safety data sheet for the article?

Not applicable

Is there classification of the article?

Not applicable

If yes, indicate the classification of the product under Regulation (EC) No

-

Enter which version of the candidate list has been used (Year, month, day)

2025-01-21

The article is covered by the RoHS Directive:

Enter the weight of the article:

No

Enter how large a proportion of the material content has been declared [%]

100

If 100% material content is not declared, please state the reason

-

If the article contains nanomaterials deliberately added to obtain a particular function, enter these here:

Has the presence of nanomaterials deliberately added to notifiable chemical products been reported to the Product Register

No

Enter the proportion of volatile organic substances [g/litre], applies only to sealants, paints, varnishes and adhesives:

Article and/or sub-components

Phase	Delivery		
Component	Bindemedel	Weight% of product	80 <x<85< th=""></x<85<>

Comment

Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
SBS modifierad asfalt		80 <x<85< td=""><td></td><td></td></x<85<>		
SBS modifierad asfalt	Bitumen destillerad	64 <x<66< td=""><td>8052-42-4</td><td></td></x<66<>	8052-42-4	
SBS modifierad asfalt	Bitumen oil (recycled)	9 <x<11< td=""><td>8052-42-4</td><td></td></x<11<>	8052-42-4	
SBS modifierad asfalt	SBS	7 <x<8< td=""><td>91261-65-3</td><td></td></x<8<>	91261-65-3	

Weight% of 1.5 <x<3 product<="" th=""><th></th></x<3>	

Comment

Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
	Polyeten	1 <x<2< th=""><th>9002-88-4</th><th></th></x<2<>	9002-88-4	
	Polypropen	0.5 <x<1< th=""><th>9003-07-0</th><th></th></x<1<>	9003-07-0	

Concentration interval (%) 6 <x<8 (%)="" (%)<="" 3<x<4="" 9<x<11="" concentration="" interval="" th=""><th>EG/CAS/Alternative designation 65997-17-3 25038-59-9 Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product</th><th>Other substance properties 9<x<11 80<x<85<="" other="" properties="" substance="" th=""></x<11></th></x<8>	EG/CAS/Alternative designation 65997-17-3 25038-59-9 Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product	Other substance properties 9 <x<11 80<x<85<="" other="" properties="" substance="" th=""></x<11>
interval (%) 6 <x<8 (%)="" 3<x<4="" 9<x<11="" concentration="" concentration<="" interval="" th=""><th>designation 65997-17-3 25038-59-9 Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative</th><th>properties 9<x<11 80<x<85<="" other="" properties="" substance="" th=""></x<11></th></x<8>	designation 65997-17-3 25038-59-9 Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative	properties 9 <x<11 80<x<85<="" other="" properties="" substance="" th=""></x<11>
Concentration interval (%) 9 <x<11 concentration<="" th=""><th>Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative</th><th>Other substance properties</th></x<11>	Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative	Other substance properties
Concentration interval (%) 9 <x<11 concentration<="" td=""><td>Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative</td><td>Other substance properties</td></x<11>	Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative	Other substance properties
Concentration interval (%) 9 <x<11 concentration<="" td=""><td>Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative</td><td>Other substance properties</td></x<11>	Weight% of product EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative	Other substance properties
interval (%) 9 <x<11 concentration<="" td=""><td>EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative</td><td>Other substance properties</td></x<11>	EG/CAS/Alternative designation 9003-07-0 Weight% of product EG/CAS/Alternative	Other substance properties
interval (%) 9 <x<11 concentration<="" td=""><td>designation 9003-07-0 Weight% of product EG/CAS/Alternative</td><td>properties 80<x<85< td=""></x<85<></td></x<11>	designation 9003-07-0 Weight% of product EG/CAS/Alternative	properties 80 <x<85< td=""></x<85<>
interval (%) 9 <x<11 concentration<="" td=""><td>designation 9003-07-0 Weight% of product EG/CAS/Alternative</td><td>properties 80<x<85< td=""></x<85<></td></x<11>	designation 9003-07-0 Weight% of product EG/CAS/Alternative	properties 80 <x<85< td=""></x<85<>
Concentration	Weight% of product EG/CAS/Alternative	
	product EG/CAS/Alternative	
	product EG/CAS/Alternative	
	product EG/CAS/Alternative	
		Other auhetenes
		Other substance
	aooignation	properties
80 <x<85< td=""><td></td><td></td></x<85<>		
64 <x<66< td=""><td>8052-42-4</td><td></td></x<66<>	8052-42-4	
9 <x<11< td=""><td>8052-42-4</td><td></td></x<11<>	8052-42-4	
7 <x<8< td=""><td>91261-65-3</td><td></td></x<8<>	91261-65-3	
	Weight% of product	6 <x<8< td=""></x<8<>
Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
6 <x<8< td=""><td></td><td></td></x<8<>		
3 <x<4< td=""><td>65997-17-3</td><td></td></x<4<>	65997-17-3	
3 <x<4< td=""><td>25038-59-9</td><td></td></x<4<>	25038-59-9	
	Mainh40/ of	9 <x<11< td=""></x<11<>
	Weight% of product	
		mun de cat

Other information:

4. RAW MATERIALS

Is there supporting documentation for the raw materials for third-party certified system for control of origin, raw material extraction, manufacturing or recycling processes or similar (for example BES 6001:2008, EMS certificate, USGBC Program)? If yes, enter system(s):

Raw materials

Total recycled material in the article



Is recycled material included in the article?

Material

Recirkulerad bitumenolja

Share of waste (from own production)

Ω

Recycled material (treated)

Recycled material

Share of waste (from other people's production)

0

Weight/percent by weight

>10 %

Comment

Renewable material

Enter proportion of renewable material in the article

Included biobased raw material is tested according to ASTM test method D6866:

Crigin of raw material For this product, there has been no withdrawal of virgin fossil material Yes If yes, please indicate the maximum percentage of virgin fossil material that can be included in the material (or item) in question 90 Wood raw materials Wood raw materials are included Included wood raw material is certified How large a proportion is certified [%]? What certification system has been used (for example FSC, CSA, SFI with CoC, PEFC)? Reference number: Enter logging country for the wood raw material and that following criteria have been met. Country of logging: Does not contain type of wood or origin in CITES appendix of endangered species Which version of CITES has been used for the check? The timber has been logged legally and there is certification for this

5. ENVIRONMENTAL IMPACT

Environmental impact during life cycle of the article, production phase module A1-A3 under EN

	, , , , , , , , , , , , , , , , , , ,
Has environmental product declaration been drawn up according t	o EN 15804 or ISO 14025 for the article?
These product-specific rules, known as PCR, have been applied:	Registration number / ID number for EPD:
The International EPD System PCR for Construction Products and CP	S-P-02107
If there is environmental product declaration or other life cycle assessme	nt, describe how the environmental impact of the article is taken into account

from a life cycle perspective:

6. DISTRIBUTION

Distribution of finished article

	Does the supplier apply any system with multiple-use packaging for the article?
	No
	Does the supplier take back packaging for the article?
	No
	Is the supplier affiliated to a system for product responsibility for packaging?
	Yes
	If yes, which packaging and which system?
	Näringslivets Producentansvar (NPA)
	Can packaging/packaging be reused?
	No
	Can packaging/packaging be recycled?
	Yes
	Can packaging/packaging be energy recycled?
	Yes
	Does the supplier use Retursystem Byggpall?
	No
	Other information:
_ (CONSTRUCTION PHASE
	Construction phase
	Does the article make special requirements in storage?
	Does the article make special requirements in storage? Yes
	Yes
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building products?
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building products? No
	Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building products?

8. USE PHASE

Use phase

9.

Does the article make requirements for input materials for operation and maintenance?
No
Specify:
Does the article require supply of energy during operation?
Not applicable
Specify:
Estimated technical service life for the article:
30-40 years
Comment:
Is there energy labelling under the Energy Labelling Directive (2010/30/EU) for the article?
Not applicable
If yes, enter labelling (G to A, A+, A+++, A+++):
If yes, enter marking (G to A)
Other information:
DEMOLITION
Demolition
Is the article prepared for disassembly (dismantling)?
Not applicable
Can the product be separated into pure material types for recycling?
No
Specify:
Does the article require special measures for protection of health and environment in demolition/disassembly?
No No
Specify:
Other information:

10. WASTE MANAGEMENT

Delivered article

Is the supplied article covered by the Ordinance (2014:1075) on producer responsibility for electrical and electronic products when it becomes waste?
No
Is reuse possible for the whole or parts of the article when it becomes waste?
No
Specify:
Is material recovery possible for the whole or parts of the article when it becomes waste?
Yes
Specify:
Uttjänt/kasserad produkt är möjlig att återvinna genom omarbetning och inblandning i råvara för tillverkning av ny produkt. Detta görs exempelvis i Holland. I vår produktionsanläggning omhändertas sedan 2014 allt produktionsspill och används som råvara för produktion av annan produkt.
Is energy recovery possible for the whole or parts of the article when it becomes waste?
Yes
Specify:
Uttjänt/kasserad produkt kan energiåtervinnas genom förbränning i godkänd förbränningsanläggning
Does the supplier have restrictions and recommendation for re-use, material or energy recovery or landfilling?
No
Specify:
Waste code for the delivered article when it becomes waste
170904 - 04 Annat blandat bygg- och rivningsavfall än det som anges i 17 09 01–17 09 03.
When the supplied article becomes waste, is it classified as hazardous waste?
No
Mounted article
Is the mounted article classified as hazardous waste?
No
Waste code for the mounted article
170904 - 04 Annat blandat bygg- och rivningsavfall än det som anges i 17 09 01–17 09 03.

Other information

11. INDOOR ENVIRONMENT

Indoor environment

mador environment			
The article is not intended for indoor use			
The article does not emit any substances			
Emissions from the article not measured			
Does the article have a critical moisture state?			
No			
If yes, state what:			
Noise	Electrical field	Magnetic fields	
Can the article give rise to own noise?	Can the article give rise to electrical fields?	Can the article give rise to magnetic fields?	
Not applicable	Not applicable	Not applicable	
Value:	Value:	Value:	
Unit:	Unit:	Unit:	
Measuring method:	Measuring method:	Measuring method:	
Paints and varnishes			
The article is resistant to fungi and algae in use in wet areas			
Emissions			

The article produces the following emissions in intended use:

Other information