

DECLARATION OF PERFORMANCE

No. **002DoP2024-04-18**

1. Unique identification code of the product-type:

Fibre Cement Flat Sheet

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

PRIMAflex™

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Flat sheets for internal and external walls and ceilings

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Saint-Gobain Prima Sdn.Bhd (Previously known as Hume Cemboard Industries Sdn.Bhd)
Lot 127220, Kawasan Perusahaan Kanthan,
31200 Chemor, Perak, Malaysia.
Tel: +605 2013688
Email: exportHCI@humecemboard.com.my

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Saint-Gobain Prima Sdn.Bhd (Previously known as Hume Cemboard Industries Sdn.Bhd)
Lot 127220, Kawasan Perusahaan Kanthan,
31200 Chemor, Perak, Malaysia.
Tel: +605 2013688
Email: exportHCI@humecemboard.com.my

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Type testing carried out by:

Product Testing Laboratory

Hume Cemboard Industries Sdn Bhd, Lot 127220, Kawasan Perusahaan Kanthan, 31200 Chemor, Perak, Malaysia.

Test Report: HCl/18/000500BA

Reaction to Fire tested by:

Bodycote Warringtonfire, Holmesfield Road, Warrington, Cheshire, WA1 2DS, United Kingdom.

Notified Body No. 0833

Classification Report No. 175517 dated 22 Sep 2008

8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Type of sheet	NT	
Mechanical resistance – Bending Strength (MoR)	Category A, Class 2	BS EN 12467:2012+A2:2018
Density	1.34 g/cm ³	
Reaction to fire	Class A1	
Water impermeability	Pass	
Water vapour permeability	Not applicable	
Dimensional variations	Level I	
Release of dangerous substances	NPD (No Performance Determined)	
Durability against warm water	R _L ≥ 0.75	
Durability against soak-dry	R _L ≥ 0.75	
Durability against freeze-thaw	R _L ≥ 0.75	
Durability against heat-rain	Pass	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Ang Show Hing, Head of R&D / QAQC/WWTP

Malaysia, 18 April 2024



(Signature)