Name of the document: Declaration of conformity Interior panel of pine, painted or white-waxed	Document nr. CPR1100	Page 1 of 2
Prepared by Elin Ahremark	Number of edition 2	
Approved by Michaela Pfeiffer	Replaces edition 2022-10-28	Date of edition 2026-09-25

DECLARATION OF CONFIRMITY – CPR1100

1. Product group and identification

Sawn, planed or profiled wooden panels with or without pine battens. The panel is top-painted or white-waxed, has a thickness ≥12 mm and fire class D-s2,d0.

2. Product information

Top-painted or white-waxed, sawn, planed, brushed or profiled wooden panel with or without battens. The panel has a thickness ≥12 mm and fire class D-s2,d0.

For additional or more detailed information about delivered product, in addition to what is stated below, see package specification or any attached commercial document.

3. The intended use of the product

Panel intended for walls and ceilings, interior use.

4. Manufacturer

Company: Moelven Wood AB
Adress: Box 8006, 650 08 Karlstad, Sweden
Telephone: +46 10 122 50 50
E-mail: order.woodab@moelven.se
Website: www.moelven.com

5. System for assessment and continuous of the product's performance

System 3 in AVCP.

6. Certification and stated performance

The product is produced according to the harmonized standard EN 14915.

The notified body MeKA (identification number 2040) has carried out fire tests to check fire growth rate, flammability and smoke growth. MeKA has issued classification report K110/2026 in accordance with EN 13501–1.

The specified standard that is followed has no replacement standard for the UK, but also applies to complying with the UKCA.

UK CA

7. Declared performance

Essential characteristics	Declared values
Reaction to fire	**Fire class** **Euro class**: D-s2,d0 according to EN 13501-1 **Substrate** **Mounting**: With non-ventilated air gap or without air gap **Minimum density [kg/m3]**: 525 **Thickness [mm]**: ≥12,5 **Fire class EN 13501-1**: A1/A2-s1, d0
Thermal conductivity	25,2 (according to EN 14915)
Application	I – Interior (according to CEN TS 15912)
Intened area of use	W C – Wall and Ceilings
Wood species	PSNY (Pine)
Durability	4 (according to EN 350-2)
Density	>480 kg/m^3
Sound absorption	0,10/0,30 (according to EN 14915)
Water vapor permeability	20 (wet) /50 (dry) (according to EN 14915)
Release of formaldehyde	E1
Content of pentachlorophenol	NPD (no performance detected)
Hazardous substances	NPD (no performance detected)
Resistant to fixing	NPD (no performance detected)

8. Additional technical documentation

The property of the product declared in section no.1 and 2 is in accordance with the property stated in section no.7. This declaration of performance is prepared under the responsibility of the manufacturer specified in Section No. 4.

Karlstad 2026-09-25

Michaela Pfeiffer, Quality- and Sustainability Manager

.....

(signature)