

DECLARATION OF PERFORMANCE

The undersigned, representing
Thermory AS (Lõõtsa 1a, Tallinn, Harju County, Estonia)
and the manufacturing plant in Reola, Tartu County, Estonia

hereby declares that the

Thermally modified and natural solid wood aspen paneling without surface coating

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product Regulation system of assessment and verification of constancy of performance: System 4 and is in accordance with the requirements of

EN 14915:2013

"Solid wood panelling and cladding – Characteristics, evaluation of conformity and marking"
Initial type testing report No.01_THERMORY_EN14915

-	1 4	D A	-	to be to	10-	1
	$-\Delta$	RA		TER		1 (
		11/7				

PERFORMANCE DECLARATION

Species European aspen (*Populus tremula*)

Intended use For interior use

Density and range of thickness 430-450 kg/m³, 10-15 mm

Reaction to fire D-s2, do (for boards with minimum thickness <12mm

valid when installed with open air gap ≤ 20mm behind)

Emission of formaldehyde E1

Content of pentachlorophenol NPD

Release of other dangerous substances NPD

Water vapor permeability NPD

Thermal resistance 0.12 W/(m K)


Sound absorption 0,1/0,3

Biological durability (according to EN 350) Class 5


CE

Simmo Soomets CEO

Tallinn 05.11.2020







DECLARATION OF PERFORMANCE No T-HB2024-Dv1

The undersigned, representing
Thermory AS (Lõõtsa 1a, Tallinn, Harju County, Estonia) and the manufacturing plant in Reola,
Tartu County, Estonia hereby declares that the

THERMALLY MODIFIED SOLID WOOD ASPEN CLADDING WITHOUT SURFACE COATING

For interior use

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product Regulation system of assessment and verification of constancy of performance: System 3 and is in accordance with the requirements of EN 14915:2013


"Solid wood paneling and cladding - Characteristics, evaluation of conformity and marking"

Testing Laboratory (Notified body No.2040)
Classification report No.K139_2024
Initial type testing report No.01_THERMORY_EN14915

CHARACTERISTIC	PERFORMANCE DECLARATION	HARMONIZED STANDARD
Species	European aspen (Populus tremula)	EN 13556:2003
Density and range of thickness	420-460 kg/m³, ≥15 mm	EN 14915:2013
Reaction to fire	D-st, d0	EN 13501-1:2018
Emission of formaldehyde	E1	
Content of pentachlorophenol	NPD	
Release of other dangerous substances	NPD	EN 14915:2013
Water vapor permeability	NPD	
Thermal conductivity	0.12 W/(m K)	
Sound absorption	NPD	
Biological durability	Class 5	EN 350:2016

Gert Zuba CQO Tallinn 14.11.2024





DECLARATION OF PERFORMANCE No HB2021-Dv1

The undersigned, representing
Thermory AS (Lõõtsa 1a, Tallinn, Harju County, Estonia) and the manufacturing plant in Reola,
Tartu County, Estonia hereby declares that the

NATURAL SOLID WOOD ASPEN CLADDING WITHOUT SURFACE COATING

For interior use

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product Regulation system of assessment and verification of constancy of performance: System 4 and is in accordance with the requirements of EN 14915:2013


"Solid wood paneling and cladding - Characteristics, evaluation of conformity and marking"

Initial type testing report No.01_THERMORY_EN14915

CHARACTERISTIC	PERFORMANCE DECLARATION	HARMONIZED STANDARD	
Species	European aspen (Populus tremula)	EN 13556:2003	
Density and range of thickness	430-450 kg/m³, 10-28 mm		
Reaction to fire	D-s2, d0		
Emission of formaldehyde	E1		
Content of pentachlorophenol	NPD		
Release of other dangerous substances	NPD	EN 14915:2013	
Water vapor permeability	NPD		
Thermal conductivity	onductivity 0.12 W/(m K)		
Sound absorption	01/0.3		
Biological durability	Class 5	EN 350:2016	

Gert Zuba CQO Tallinn 05.03 2024





DECLARATION OF PERFORMANCE No HB2021-Dv1

The undersigned, representing
Thermory AS (Lõõtsa 1a, Tallinn, Harju County, Estonia) and the manufacturing plant in Reola,
Tartu County, Estonia hereby declares that the

NATURAL SOLID WOOD ASPEN CLADDING WITHOUT SURFACE COATING

For interior use

is in conformity with the provisions of the EC Regulation No 305/2011 Construction Product Regulation system of assessment and verification of constancy of performance: System 4 and is in accordance with the requirements of EN 14915:2013

"Solid wood paneling and cladding - Characteristics, evaluation of conformity and marking"

Initial type testing report No.01_THERMORY_EN14915

CHARACTERISTIC	PERFORMANCE DECLARATION	HARMONIZED STANDARD
Species	European aspen (Populus tremula)	EN 13556:2003
Density and range of thickness	430-450 kg/m³, 10-28 mm	
Reaction to fire	D-s2, d0	
Emission of formaldehyde	El	
Content of pentachlorophenol	NPD	
Release of other dangerous substances	NPD	EN 14915:2013
Water vapor permeability	NPD	
Thermal conductivity	0.12 W/(m K)	
Sound absorption	01/0.3	
Biological durability	Class 5	EN 350:2016

Gert Zuba CQO Tallinn 05.03.2024



Certificate





NEPCon OÜ hereby confirms that the Chain of Custody system of

Thermory AS

Peterburi tee 44 11415 Tallinn Estonia

has been assessed and certified as meeting the requirements of PEFC ST 2001:2008 (Second edition); PEFC ST 2002:2013 (Second edition)

The certificate is valid from 25-04-2018 to 24-04-2023 Certificate version date: 18-10-2018

Scope of certificate

Certificate type: Single Chain of Custody

Certificate registration code NC-PEFC/COC-000132

> Justinas Janulaitis Operations Director Filosoofi 31, Tartu Estonia

An EAK accredited products certification body Reg. No PC025.

Products offered, shipped or sold by the certificate holder can only be considered covered by the scope of this certificate when the required PEFC claim is clearly stated on delivery documents.

The physical printed certificate remains the property of NEPCon OÜ and shall be returned upon request.



Annex A: Scope of Thermory AS PEFC Chain of Custody Certificate NC-PEFC/COC-000132

Product Group	PEFC Claims	CoC Method	Input Material Category	
01030 - Chips and particles	PEFC Controlled Sources	Physical separation	Certified material; Other material	
01040 - Wood residues	PEFC Controlled Sources	Physical separation	Certified material; Other material	
02010 - Fuelwood (incl chips, residues, pellets, brickets, etc.)	PEFC Controlled Sources	Physical separation	Certified material; Other material	
03020 - Sawnwood	x% PEFC Certified	Physical separation	Certified material	
04020 - Finger Jointed Lumber	x% PEFC Certified	Physical separation	Certified material	
04030 - Glue Laminated Products	x% PEFC Certified	Physical separation	Certified material	
08034 - Flooring	x% PEFC Certified	Physical separation	Certified material	
08040 - Decorative wood	x% PEFC Certified	Physical separation	Certified material	
09020 - Garden Furniture/Outdoor Products	x% PEFC Certified	Physical separation	Certified material	
09022 - Playground equipment	x% PEFC Certified	Physical separation	Certified material	
09023 - Terrace planks	x% PEFC Certified	Physical separation	Certified material	
09030 - Lining, weather board	x% PEFC Certified	Physical separation	Certified material	

Products offered, shipped or sold by the certificate holder can only be considered covered by the scope of this certificate when the required PEFC claim is clearly stated on delivery documents.

The physical printed certificate remains the property of NEPCon OÜ and shall be returned upon request.

Certificate version date: 18-10-2018



Annex B: Scope of Thermory AS PEFC Chain of Custody Certificate NC-PEFC/COC-000132

No	Site Name	Address	Sub-code	
1	Thermory AS tootmine Reolas	Vilja tee 14 61707 Reola Tartu County Estonia	N/A	
2	Thermory AS Matsu terminal	hermory AS Matsu terminal Vana-Narva mnt 2d Tallinn Estonia		
3	Thermory AS Peterburi tee 44 11415 Tallinn Estonia		N/A	
4	Thermory AS tootmine Lool	Saha tee 25 74201 Loo Harjumaa Estonia	N/A	

Products offered, shipped or sold by the certificate holder can only be considered covered by the scope of this certificate when the required PEFC claim is clearly stated on delivery documents.

The physical printed certificate remains the property of NEPCon OÜ and shall be returned upon request.