

English.....	2
Svenska.....	3
Norsk.....	4
Dansk.....	5
Suomi.....	6
Deutsch.....	8
Netherlands.....	10
Français.....	12
Italiano.....	14
Español.....	15
Português.....	17
Ελληνικά.....	18
Polski.....	20
Eesti.....	22
Lietuviškai.....	23
Latviski.....	25
Русский.....	27

Limit 1001 HV

Cross Line Laser with one horizontal and one vertical line. The vertical line reaches 115 degree up over your head. Magnetic damping compensator. Mode switch for separate lines or off self leveling to show a sloping line. Mechanical locking for prevent vibrations.

Contents : Laser, Multi function bracket for assembling on wall or on a tripod, target plate, soft bag, batteries and manual.

Safety. Do not stare into the laser beam or view directly with optical instruments. It can cause devastating damage to your eyes. Place never instrument at eye level.

Care and Handling. This is a precision instrument and must be treated accordingly. Avoid impact, dropping and vibration. Push switch/locking key Off during transport. Use and store the instrument within the specified temperature range. Remove the batteries if the laser should not be used for a long time. Clean with a soft, dry cloth.

Specification :

2 pc laser diodes class 2M, 15 mw 635 nm.

Self leveling range		$\pm 3^\circ$
Accuracy	mm	$\pm 3 \text{ mm}/10\text{m}$
Protected class	IP	54
Battery		3 pc type AA
Operation time	Hour	10
Operation temperature	$^\circ\text{C}$	-10...+50
Thread		1/4"
Dimension	mm	90x90x65
Weight	gram	365

Start. Slide the key, placed on front side to the right.

Off. Slide the switch/locking key to the left.



Toggle Horizontal-Vertical-Horizontal/Vertical-Self leveling Off. The laser line will be off if the laser is tilted beyond self-leveling range.



Pulse Signal. For outdoor or bright environments with laser receiver (Optional). Laser Receiver lines indicate visual and audible signal. Range 35 meters.

Battery. Battery cover is placed on the back side.