Product Information Sheet

without

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS
Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL
BA-d-l:d-wife 02000400000

Supplier's addre	ess: Customer Ca	are Philips, I.B.R.S./C	C.C.R.I. /Numéro 10461,	5600VB Eindhoven, NL
Model identifie	r: 9290018900C			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		E27		
(or other electric interface)				
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P _{on}), expressed in W		4,3	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	106	Spectral power	See image
dimensions	Width	60	distribution in the	in last page
عاده ماعانا		-	-	

60

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	40			
		Chromaticity	0,458			
		coordinates (x and y)	0,410			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	1	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

