Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS
Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL
Model identifier: 9290023703

Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	Product pa	arameters	ı
Darameter	Value	Darameter	Value

Parameter Value Parameter Value **General product parameters:** F Energy consumption in on-2 Energy efficiency mode (kWh/1000 h), rounded class up to the nearest integer Useful luminous flux (фuse), 136 in Correlated colour 2 700 indicating if it refers to the flux Sphere (360°) temperature,

in a sphere (3	60º), in a wide n a narrow cone	зрпете (300)	rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	
On-mode pressed in W	oower (P _{on}),	1,4	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expre	idby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	78	Spectral power	See image
dimensions	Width	45	distribution in the	in last page
without	Depth	45		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	15			
		Chromaticity	0,458			
		coordinates (x and y)	0,410			
Parameters for LED and OLED li	ght sources:					
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

